

# NORFAB ALUMINIZED CLOTH

A Norfab woven medium weight fabric of an Aramid fiber blend over a fiberglass core yarn. Applications include safety clothing, gloves, mitts, jackets, curtains, and other industrial applications. Resistant to reflective heat, offers excellent thermal, splatter and molten metal splash protection.

## About NOR\*FAB Corporation

NOR\*FAB manufactures textile products using flame resistant synthetic fibers suited for use at high temperatures and for personal protection. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. NOR\*FAB uses para-aramid, meta-aramid, melamine, phenolic, oxidized PAN, flame resistant rayon, polybenzimidazole, and other technical fibers blended into unique yarns which provide high levels of heat protection and insulation.

NOR\*FAB produces many of these yarns on the DREF Spinning System for use in the weaving, knitting, gasket, and wire & cable industries. NOR\*FAB possesses the largest collection of DREF III spinning frames of any yarn manufacturer in the world.

**Among its offerings, NOR\*FAB boasts fabric lines for the following end uses:**

### **Firefighting**

OMNI Vantage™, OMNI Elite®, OMNI 45™, and OMNI Quilt™

### **Electric Arc Protection**

NF Arc™, ArcWeld®

### **Welding Protection**

ArcWeld®

### **Cut Protection**

CutPro®

**Since 1979**

*Proud American Manufacturers of Flame Resistant Textiles*

## NORFAB Aluminized Fabric Specifications

<b>Style</b>	<b>22PT30- - AL1</b>
<b>Base Fabric</b>	Aramid/Fiberglass
<b>Color/Appearance</b>	Aluminized 1 side, Yellow reverse
<b>Style</b>	Plain
<b>Fabric Weight, oz./sq yd, average</b>	24 (815 gm/sq.m)
<b>Fabric Thickness, inches</b>	0.065 (+/-0.005") (1.65mm)
<b>Warp Strength, lbs/in.</b>	300.0 (136 Kg/2.54 cm)
<b>Fill Strength, lbs/in.</b>	200.0 (90 Kg/2.54 cm)
<b>Abrasion Resistance</b>	Very Good
<b>Coating/Lamination</b>	Aluminized Mylar film
<b>Sunlight &amp; Age Resistance</b>	Base fabric is UV sensitive
<b>Finish Number</b>	Aluminized Mylar film laminate; See Fabric Finish Options data sheet



1310 Stanbridge Street,  
Box 830, Norristown, PA 19404-0830 U.S.A.  
Tel: 610-275-7270 • 800-441-9680 • Fax: 610-277-6106  
Email: sales@norfab.com • www.norfab.com